PARTNER


CARE . TRUST . RESPONSIBILITY

LABEL PRINTER LP-1625

ONE FOR ALL







SPECIAL FEATURES

Thermal transfer and direct thermal print technology
Easy media loading
Transmissive and reflective dual sensor for accurate detection
Serial USB Parallel Ethernet connectivity available
300meters large ribbon capacity
External holder available for option

TECHNICAL DATA

CARE . TRUST . RESPONSIBILITY

LP-1625

MODELL	LP-1625	
Print Method	Thermal Transfer / Direct Thermal	
Interface	USB, parallel, serial, Ethernet	
Print Speed	2-6"" per second (51-152mm/sec)	
Print Width	4,09" 104mm	
Print Length	90"" 2286mm max.	
Emulation	ZPL / TSPL	
Resolution	203dpi	
Paper Width	0,78-4,72" 20-120mm	
Memory	TSPL: RAM: 8MB Flash: 4MB	ZPL: RAM: 16MB Flash: 8MB
Media Diameter	5" max.	
Ribbon Outside Diameter	67mm max	
Ribbon Length	300m max	
Ribbon Width	30mm min., 110mm max.	
Ribbon core inner Diameter	1" 25,4mm	
Cutter y/n	Available for option	
Barcode type	1D: Code 39,Code 93,ITF,EAN 128, Code 128 subsets A,B,C,Codabar,JAN-8(EAN-8),JAN-13(EAN-13),UPC-A,UPC-E, EAN and UPC 2(5) digits add-on, MSI,MSIC,PLESSEY,CPOST,ITF 14,EAN 14, 2D: 2D Pharmacode, Aztec, Codeblock F, Datamatrix, Grid Matrix, GS 1 Datamatrix, Maxicode, MicroPDF, PDF-417, QR, Micro QR, GS 1 QR Code, DotCode, GS 1 DotCode, BMP&PCX	
Printer weight	2,09kg	
Dimension	278x210x180mm (WxDxH)	
PS	external power adapter	
Operation Condition	Operation Condition Temperature: 5-45°C, Humidity: 25-85%RH	Storage Condition Temperature: -10-50°C, Humidity: 10-90%RH
Image	PCX. BMP	
Paper type	Thermal & Non-Thermal-Paper (like cloth tags, washing labels, silver labels and lables based on e.g. PP or PE), continuous paper, paper with interspaces, folding paper, black mark paper	
Paper rolling up method	Printing side outward rolling / inward rolling	
The thickness of the paper	Max.0.254 mm(10 mil) Min.0.06 mm(2.36 mil)	
Gap size	Min.2 mm(0.09")	
Driver	Windows 2000 XP Vista Windows 7/8/8.1/10 Windows Server 2003&2008	
Software	Labelshop	
Agency Approvals	CE, FCC, CB, BIS, RoHS	

CARE . TRUST . RESPONSIBILITY

EUROPE	+49 40 450 635-0	info@partner-tech.eu
UNITED KINGDOM	+44 1928 579 707	sales-uk@partner-tech.eu
IBERIA	+34 913 120632	comercial@partner-tech.eu
ADRIA	+386 1 566 25 20	prodaja@partner-tech.eu

*Specifcation is subject of change without prior notice.
Subject to alterations Aug. 2017